DAELIM
DaelimOPP

DAELIM Industrial Co., Ltd.
Petrochemical Division
5F KCC Bldg. 45 Namdaemunro 4-ga,
Jung-gu Seoul, Korea

CERTIFICATE OF ANALYSIS

ISSUED NO FM-2019-1225
GRADE EGM252
ISSUED DATE 2019-04-16

ITEM	UNIT	METHOD	SPEC.	RESULT
THICKNESS AVERAGE_ACT	㎛	DIC	24.25 ~ 25.75	24.25
TENSILE STRENGTH_MD	kg/㎟	ASTMD882	Min 6.00	6.80
TENSILE STRENGTH_TD	kg/㎟	ASTMD882	Min 9.00	10.30
TENSILE ELONGATION_MD	%	ASTMD882	Max 210.00	178.00
TENSILE ELONGATION_TD	%	ASTMD882	Max 80.00	71.00
HAZE	%	ASTMD1003	Min 75.00	91.80
GLOSS_60°	-	ASTMD2457	Max 9.00	9.00
WETTING TENSION_INSIDE	dyne/cm	ASTMD2578	Min 44.00	48.00
WETTING TENSION_OUTSIDE	dyne/cm	ASTMD2578	Min 38.00	41.00
INI. SEAL. TEMP.	℃	DIC	90.00 ~ 120.00	
SEALING. STRENGTH	g/25mm	DIC	Min 600.00	1110.00
----- BLANK ----				
LOT NO				

CERTIFY THE STATEMENT OF QUALITY TO BE TRUE AND CORRECT.

DAELIM INDUSTRIAL CO.,LTD. CHONJU PLANT

843 Yongam-ri Bongdong-eup Wanju-gun Jeon-buk, Korea
Tel) 82-63-260-1114 Fax) 82-063-261-0149

APPROVED BY : J . Y , JEONG / MANAGER
Film Quality Assurance Team

김병우
DAELIM INDUSTRIAL CO., LTD.
N. W Park
PARK NO WOONG / SENIOR VICE PRESIDENT
PETROCHEMICAL DIVISION

필름영업1팀//임성빈